



	QUEST [®]	GO GO [®] ULTRA X	GO GO [®] ELITE TRAVELLER PLUS	GO GO [®] LX W/ CTS SUSPENSION	GO GO ENDURANCE LI [®]	ZERO TURN 8	REVO [®] 2.0	ZERO TURN 10	PATHRIDER [®] ES10	PATHRIDER [®] 10	PATHRIDER [®] 10 DX	GOPHER SV	VICTORY [®] 10 LX W/ CTS SUSPENSION	CELEBRITY [®] DX	CELEBRITY [®] XL DX	MAXIMA	PATHRIDER [®] 130 XL	PATHRIDER [®] 140 XL	CELEBRITY MFP	OUTBACK [®]	SPORT RIDER
RANGE PER CHARGE (MAX) ^{2, 8}	Up to 19.3 km	3W: Up to 11 km 4W: Up to 11.5 km	Up to 20.9 km ⁹	Up to 16.9 km ⁹	Up to 23 km	Up to 16 km	Up to 21 km	Up to 28.8 km	Up to 17.9 km	Up to 25 km	Up to 25 km with 40AH	Up to 24 km	Up to 26 km	Up to 20.6 km	Up to 40.2 km ¹⁵	3W: Up to 31.4 km 4W: Up to 31.4 km	Up to 25 km	Up to 35 km	Up to 43.5 km	Up to 35 km	Up to 35 km
MAXIMUM WEIGHT CAPACITY	113.3 kg	118 kg	136 kg	136 kg	147 kg	136 kg	170 kg	170 kg	158.7 kg	158.7 kg	158.7 kg	160 kg	181.4 kg	158.7 kg	158.7 kg	226.8 kg	158.7 kg	181.4 kg	159 kg	158.7 kg	181.4 kg
TURNING RADIUS ³	82 cm	3W: 83.8 cm 4W: 100.3 cm	116.2 cm	116.2 cm	122.5 cm	97.2 cm	132.1 cm	109 cm	132 cm	137 cm	133.3 cm	143 cm	152 cm	3W: 105.4 cm 4W: 149.8 cm	168.2 cm	3W: 124.5 cm 4W: 134.6 cm	170 cm	210 cm right 208 cm left	138 cm	243 cm	158 cm
MAXIMUM SPEED ¹⁷	Up to 6 km/h	Up to 6.4 km/h	Up to 7.2 km/h	Up to 7 km/h	Up to 6.7 km/h	Up to 6.4 km/h	Up to 8 km/h	Up to 10 km/h	Up to 8.85 km/h	Up to 8.4km/h	Up to 8.85 km/h	Up to 10 km/h	Up to 9 km/h	Up to 9.65 km/h	Up to 10 km/h	Up to 9.3 km/h	Up to 10 km/h	Up to 10 km/h	Up to 10 km/h	Up to 10 km/h	Up to 10 km/h
LENGTH & WIDTH ^{3, 11}	L: 92.7 cm W: 49.5 cm	3W: L: 94 cm 3W W: 49.5 cm 4W: L: 100.3 cm 4W W: 49.5 cm	L: 102.3 cm W: 54 cm	L: 104 cm W: 52.1 cm	L: 107 cm W: 52 cm	L: 116 cm W: 50.8 cm	L: 119.4 cm W: 52.7 cm	L: 122 cm W: 61.6 cm	L: 115.6 cm W: 57.1 cm	L: 115 cm W: 56.5 cm	L: 119.4 cm W: 56.2 cm	L: 119.4 cm W: 59 cm	L: 119.4 cm W: 56.5 cm	3W L: 116.8 cm 3W W: 61 cm 4W L: 118.7 cm 4W W: 61 cm	L: 130.2 cm W: 64.1 cm	3W L: 120.7 cm 3W W: 68.6 cm 4W L: 120.7 cm 4W W: 68.6 cm	L: 136 cm W: 63.6 cm	L: 142.8 cm W: 69.2 cm	L: 145 cm W: 70.7 cm	L: 156 cm W: 83 cm	L: 165 cm W: 78 cm
SEAT TYPE (STANDARD) ⁵	Compact, Foldable, Molded Plastic, 41 cm x 33 cm (16"x13")	Compact, Foldable, 43 cm x 43 cm (17" x 17")	Compact, Foldable, 43 cm x 43 cm (17" x 17")	Compact, Foldable, 43 cm x 43 cm (17" x 17")	Compact, Foldable 43.1 cm x 43.1 cm (17" x 17") 50.8 cm x 45.7 cm (20" x 18")	Compact, Foldable, 43 cm x 43 cm (17" x 17")	Compact, Foldable, 43 cm x 43 cm (17" x 17")	Pillow Top Deluxe H-B w/sliders 49.5 cm x 44.5 cm (19.5" x 17.5")	Foldable Molded Plastic 46 cm x 43 cm (18" x 17")	Foldable Molded Plastic 46 cm x 43 cm (18" x 17")	CRS Junior Seat 44.25 cm x 43 cm (17.5" x 17")	Foldable Molded Plastic 48 cm x 42 cm (19" x 16.5")	Reclining H-B w/ Sliders & Headrest 46 cm x 46 cm (18" x 18")	Deluxe Reclining H-B w/ Sliders & Headrest 46 cm x 46 cm (18" x 18")	Deluxe Reclining H-B w/ Sliders & Headrest 46 cm x 46 cm (18" x 18")	Adjustable H-B w/ Black Vinyl 55.9 cm x 50.8 cm (22" x 20") ²	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5" x 17.5")	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5" x 17.5")	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5" x 17.5")	Pillow Top Deluxe H-B w/Sliders 49.5 cm x 44.5 cm (19.5" x 17.5")	Captains High-Back Adjustable Seat 51 cm x 56 cm (20" x 22")
SEAT-TO-DECK HEIGHT RANGE	31 cm Fixed	40 cm - 43.8 cm	41.3 cm - 45 cm	41.3 cm - 43.8 cm	41.2 cm x 45 cm	40.6 cm - 45.6 cm	38.1 cm - 45.7 cm	47.5 cm - 52.5 cm	37 cm - 42 cm	37 cm - 42 cm	43.8 cm - 47.6 cm	44.5 cm - 48.3 cm	46 cm - 49 cm	41 cm x 44.5 cm	43.2 cm x 53.3 cm	44 cm x 60 cm	42 cm - 47 cm	47 cm	45.2 cm	50 cm - 53 cm	47.5 cm
SEAT-TO-GROUND HEIGHT RANGE	51 cm Fixed	55 cm - 60 cm	52 cm - 55.88 cm	52.7 cm - 56.5 cm	53.9 cm x 57.7 cm	53.3 cm - 60 cm	53.3 cm - 60 cm	58.4 cm - 63.5 cm	51.4 cm - 55.2 cm	52 cm - 55.8 cm	60 cm - 63.8 cm	61 cm - 64 cm	60 cm - 64.8 cm	58.5 cm x 61.5 cm	54 cm - 64 cm	56.6 cm - 72.6 cm	56.7 cm	66.7 cm - 70.5 cm	66.7 cm - 70.5 cm	76 cm - 80 cm	24.8 cm
GROUND CLEARANCE ^{3, 12, 14}	5.8 cm at frame	6.3 cm at midframe 3.8 cm at motor	7.62 cm at frame	6.4 cm at frame 3.8 cm at motor	3.6 cm at motor	8.9 cm at frame 3.3 cm at motor	8.9 cm at frame 3.2 cm at motor	5 cm at motor	8.8 cm at frame	7.6 cm at frame	8.25 cm at frame	4 cm at rear frame	5.6 cm at motor	8.25 cm at transaxle	10.8 cm at transaxle	5.7 cm at motor	9 cm at transaxle	13.3 cm at midframe	8.8 cm at motor	14 cm at midframe	12.7 cm at shroud
OVERALL WEIGHT (NOT INC. BATTERY) ^{3, 13}	23.5 kg	3W: 34.5 kg 4W: 36.3 kg	39.4 kg	39.4 kg	42.4 kg	53.9 kg	60 kg	82 kg	59.4 kg	62.4 kg	84.8 kg	68.9 kg	81.2 kg	3W: 70.7 kg 4W: 75 kg	112 kg	3W: 86.4 kg 4W: 92 kg	99.8 kg	117.7 kg	104.3 kg	124 kg	115 kg
WEIGHT OF HEAVIEST PIECE ³	23.5 kg (does not disassemble)	3W: 13.4 kg 4W: 15.4 kg (front sections)	15.4 kg (front section)	16.6 kg (front section)	18.48 kg (front section)	21.8 kg (rear section)	25.9 kg (front section)	34 kg (rear section)	25.8 kg (front section)	27.7 kg (rear section)	29.5 kg (front section)	50.8 kg (main frame - does not disassemble)	35.2 kg (rear section)	3W: 27.5 kg 4W: 32 kg (front section)	37.6 kg (front section)	3W: 61.7 kg 4W: 67.3 kg (main frame - does not disassemble)	34 kg (rear section)	93 kg (main frame)	94 kg (main frame - does not disassemble)	99 kg (main frame)	92.3 kg (main frame)
SUSPENSION	N/A	N/A	N/A	CTS Front & Rear	CTS Front & Rear	CTS Front & Rear	Front & Rear	Front & Rear	N/A	N/A	Front & Rear	Front & Rear	Front & Rear	3W: Rear 4W: Front & Rear	Front & Rear	N/A	Front & Rear	Front & Rear	Front & Rear	Front & Rear	Front & Rear
3W/4W OPTION	4W	3W & 4W	4W	4W	4W	4W	4W	4W	4W	4W	4W	4 W	4W	3W & 4W	4W	3W & 4W	4W	4W	4W	4W	3W
FRONT TYRES	1.5" x 7" solid	3W: 2" x 8" solid 4W: 2" x 7" solid	2" x 8" solid	2" x 7" solid	2" x 8" solid	2" x 7" solid	2.5" x 9" solid	9" x 2.75" solid	3.6" x 10.4"	3.5" x 10"	3.5" x 10"	3" x 10"	3.5" x 10"	3.5" x 10"	4" x 13"	3.6" x 10" solid	4" x 13"	4" x 13"	13"	14.5" x 6"	2.75" x 19" ¹⁶
REAR TYRES	1.9" x 7.8" solid	2.5" x 8" solid	3" x 9" solid	2.5" x 8" solid	2.5" x 8" solid	2.5" x 9" solid	2.5" x 9" solid	10.75" x 6" solid	3.6" x 10.75" solid	3.5" x 10"	4" x 10"	3" x 10"	3.5" x 10"	4" x 10"	4" x 10"	3.6" x 10.75" solid	4" x 13"	4" x 13"	32.8 cm (13")	14.5" x 6"	2.75" x 19" ¹⁶
BATTERY REQUIREMENTS ⁶	(1) 11.5 AH (Lithium Ion)	(2) 12AH	(2) 18AH	(2) 18AH	16AH (Lithium Ion)	(2) 22AH	(2) 31AH	(2) 40AH	(2) 31AH	(2) 31AH or (2) 40AH	(2) 31AH or (2) 40AH	(2) 40AH	(2) 40AH	(2) 31AH or (2) 40AH	(2) 40AH	(2) 50AH	(2) 55AH	(2) 70AH	(2) 70AH	(2) 100AH	(2) 70AH
BATTERY CHARGER	Off-Board 2.5A (Lithium Ion)	Off-Board, 2A	Off-Board, 2A	Off-Board, 2A	Off-board, 3.5A (Lithium Ion)	Off-Board, 3.5A	Off-Board, 3.5A	Off-Board, 3.5A	Off-Board, 3A	Off-Board, 3A	Off-Board, 3A (32AH) Off-Board, 5A (40AH)	Off-Board, 5A	Off-Board, 5A	Off-Board, 5A	Off-Board, 5A	Off-board, 5A	Off-Board, 8A	Off-Board, 8A	Off-Board, 8A	Off-Board, 8A	Off-Board, 8A
BATTERY WEIGHT ¹⁰	2.3 kg	4 kg ⁴	6 kg ⁸	6 kg ⁷	5.4 kg	6 kg ⁷	11 kg	14 kg	10.5 kg	10.5 kg or 14 kg	10.5 kg or 14 kg	14 kg	14 kg	10.5 kg or 14 kg	14 kg	16.6 kg	16.8 kg	23.45 kg	22 kg ⁵	27.9 kg	23.7 kg
COLOUR OPTIONS	White	Red	Red, Blue ¹	Red, Blue ¹	Garnet Red, Euro Grey	Fire Opal, Pearl White, Sapphire Blue	Grey Street, True Blue	Candy Apple Red	Red	Viper Blue	Viper Blue	Red	Candy Apple Red	Candy Apple Red	Candy Apple Red, Silver	Garnet Red, Ocean Blue	Candy Apple Red, Mercury Silver	Candy Apple Red, Yellow, Silver	Red, Blue	Stone Grey	Black

¹ All shroud panels included. ² Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%. ³ Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3%. ⁴ 12 AH battery pack weighs 8.8 kg (19.5 lbs.). ⁵ Durable solid plastic. ⁶ Deep cycle (AGM or gel cell type recommended) excluding Lithium-ion models. ⁷ 18 AH battery pack weighs 13.4 kg (29.5 lbs.). ⁸ Tested in accordance with ANSI/RENSA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. ⁹ Up to 14 miles per charge on 18 AH batteries. ¹⁰ Battery weight may vary based on manufacturer. ¹¹ Width of base (not including seat). ¹² Does not account for anti-tip clearance. ¹³ Includes standard seat weight. ¹⁴ At midframe ¹⁵ Range tested with 31-36 AH Batteries. Standard larger battery size would increase range. ¹⁶ 6.9 cm x 35.5 cm (2.75" x 14") Rim Only ¹⁷ Varies with user weight, terrain type, battery charge, battery condition and tire condition. This specification can be subject to a variance of (+ or -) 10%. **NOTE** The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice. Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.